by Boxlight®

clevertouch.com



UX Pro Edge

Push collaboration to the edge facilitated by FlatFrog In-Glass™ Technology

The Ultimate Meeting Room Solution

A total transformation for collaboration in the workplace.

UX Pro Edge facilitates FlatFrog InGlass edge-to-edge
technology to create a unique user experience.

20W speakers and 2x 10W subwoofers for a crystal clear audio experience.

Front-mounted 2x

EDLA Certified •

NEW

Access the Google Play Store and Google Workplace, along with the full Microsoft 365 suite, directly from the screen.





Available in a range of sizes 65" 4K | 75" 4K | 86" 4K

Integrated Camera

4K display optimized by your choice of input source. Features 48MP Pixel and 90°

NEW

FOV with 5M distance focus, ePTZ and face detection auto tracking.

• Hotkeys

Embedded quick

launch digital buttons

on the screen.

Any Screen,Any Time

Integrated NFC
delivers flexibility to
log in to any connected
Clevertouch anywhere
in the world with the
users personal profile.



Why Choose FlatFrog's InGlass ™ technology?

Uncompromised Writing Performance for Digital Whiteboarding

The most natural and accurate writing experience that is as easy as using a traditional whiteboard. InGlass'sTM optical emitters and detectors allow for a real time no-lag experience



Natural pen-onpaper experience



Passive pen no charging



Calligraphy writing with a brush



Palm rejection



Precision eraser using finger, palm or eraser

Pushing the EDGE for an optimised user experience





Collaboration Tools at your fingertips



Enhanced Boardroom Collaboration



Connect to CleverCast with one tap

What's New?



FlatFrog



Anti Bacterial Glass

Flat Frog InGlass Edge to Edge

Top Mounted Camera















2x 10W Subwoofers

8GB RAM & 128GB ROM

Android 13

Google Enterprise Partner

Key Features





Includes 2x CleverCast USB-C devices. Plug into your laptop and screenshare, use and control all connected devices instantly



Award winning digital signage is included at no extra cost



Embedded quick launch digital buttons on the screen



Experience the virtual collaboration camera quality with your choice of input source.



Add an Intel Windows 10 Pro i5 or i7 OPS, enabling you to load your existing apps and software from your network



Highly secure with the option to lock down settings and functionality.



The UX Pro allows you to completely customise your home screen with your company branding, logos and news



Integration with your current system set up is easy

UX Pro Edge Specifications

Display

| Diagonal Size | 65" 4K, 75" 4K, 86" 4K | |
|------------------------|---|--|
| Screen Type | LCD | |
| Aspect Ratio | 16:9 | |
| Display Colours | 1.07 Billion (10 bit) | |
| Resolution | 4K UHD (3840x2160 @60Hz) | |
| Response Time | 3ms | |
| Refresh Rate | 60Hz | |
| LCD Viewing Angle | 178° | |
| Brightness | 400 cd/m2 | |
| Contrast Ratio | 4000:1 | |
| Dynamic Contrast Ratio | 6000:1 | |
| Glass Hardness | AG Tempered Glass - Mohs Level 7 | |
| Glass Type | Low Parallax 1mm Air Gap - Heat tempered - Anti Glare & Anti Smudge for durability - Supe Glide Surface | |
| Main Board | RK3588 | |
| Life of Screen | 50,000 Hours | |
| NTSC | 72% | |

Interactivity

| Writing Technology | Flat Frog InGlass Technology - M5 | |
|-----------------------------|---|--|
| NEW Continuous Touch Points | 40 | |
| Touch Resolution | 32768x32768px | |
| Response Time | ≤10ms | |
| Touch Accuracy | ±1mm | |
| Minimum Object Size | 2mm | |
| Touch Tool | Finger, passive pen, opaque objects | |
| Simultaneous Writing | Yes | |
| Ink In Tools | Yes - Lynx | |
| Pens Included | 2 | |
| NEW Pen Type | Dual Recognition Stylus Flat Frog Technology | |
| Pen Holder | Integrated magnetic pen holders | |
| Pen Tip Diameter | 3mm/7mm | |
| Pen & Touch Differentiation | Yes | |
| Pen Identities | 2 | |
| Palm Rejection | Yes | |
| Annotation Over Any Source | Yes | |
| Classroom Essential Apps | Includes Whiteboard, Annotate, Timer, Media Players, Browser, PDF Reader, Screen Record, Spinner, Voting, Maths Tools | |
| Compatibility* | Windows, Linux, Mac, Android, Chrome | |
| Tracking Rate | ≥1m/s | |
| Scan Rate | ≥100hz | |
| Gestures & Edge Swipes | Windows Supported, OSX with additional Driver | |

Connectivity

| OPS Slot | 80Pin Windows/Android | |
|---|---|--|
| HDMI In | 3 | |
| HDMI Out | 1 | |
| USB-A 2.0 | 3 | |
| USB Touch (type B) | 3 | |
| NEW USB A 3.0 (faster data transfer) | 2 x USB Front Type A 3.0 with faster data transfer 2 x USB Side Type A 3.0 with faster data transfer | |
| NEW USB C (Video, Audio & Touch) | 1 x USB Side Type C with video, audio, touch & network 1 x USB Front Type C with video, audio, touch, net- work, and 100W charging | |
| NEW USB C (Data Transfer) | 1 x USB Top Type C Supports data transfer for top mounted camera | |
| NEW USB C Out | 1 x USB Type C Out with video, audio, touch and network | |
| LAN In (RJ45) | 1 | |
| LAN Out (RJ45) | 1 | |
| RS-232 | 1 | |
| Wake-on-Lan | Yes | |
| Wireless Adapter 2.0 + WAP | Upgraded | |
| Clevertouch WiFi Module | Yes | |
| Bluetooth | Yes – 5.0 | |
| Audio In | 1 | |
| Optical Out | 1 | |
| Headphone | 1 (3.5mm) | |
| Total touch out ports | 3 | |
| NFC Reader / Writer | Yes - Integrated | |
| Camera | Yes - Integrated | |
| Proximity Sensor | Yes | |
| NEW WiFi | IEEE 802.11a/b/g/n/ac/ax with 2 × 2 MIMO (hotspot only) (both 2.4 and 5 GHz bands) | |
| WiFi Speed | Capable of speeds up to 433Mbps | |
| | | |

Computing

| NEW Operating System | Android 13 | |
|-------------------------|-------------------------------|--|
| NEW System Version | LUX 13 | |
| NEW RAM | 8GB | |
| NEW Internal Storage | 128GB | |
| CPU | Quad Core A76 + Quad Core A55 | |
| GPU | Mali G610 MC4 | |
| Android Resolution | 4K | |
| Android Module Slot | No | |
| Integrated LUX UI | Yes | |
| NEW System Architecture | 64-bit | |

UX Pro Edge Specifications

Power

| Power Requirements | 100-240V ~ 50/60Hz | |
|-----------------------------|--------------------|--|
| Power Consumption (Normal) | TBD | |
| Power Consumption (Standby) | ≤0.5W | |
| Ultra Quiet Fanless Design | Yes | |

Operating & Storage Environment

| Operating Temperature | 0° to 40° | |
|-----------------------|-------------------|--|
| Storage Temperature | -20° to 60° | |
| Operating Humidity | 10% to 90% RH | |
| Storage Humidity | 10% to 90% RH | |
| Altitude | Below 5000 metres | |

Audio

| NEW Dual Front Facing, Bass Enhanced Speakers | 2 x 20W Speaker + 2 x 10W Subwoofer |
|--|--|
| Audio Out | Yes |
| SPDIF / Fibre | Yes |
| Sound Channel | 2.2 |
| Line Array Microphone (noise cancelling) | 8-Array |
| Super Wide Sound | Yes |

UX Pro Edge Built-In Features

| Embedded Digital Signage | Yes |
|---|--|
| Clevershare™ Mirroring Any Device To The Board | Free for the life of the screen (touch back) |
| Integrated Personalised Account Profiles | Yes |
| Cloud Account Access | OneDrive, Google Drive, LYNX Cloud |
| Embedded Room Booking | Yes |
| Whiteboard Annotation | Yes |
| Email Out Direct From Touchscreen | Yes |
| Scan QR Code For Saving Work | Yes |
| Alerts and Announcements | Yes |
| Over-the-Air Updates | Yes |
| Remote Management Of Touchscreens (MDM) | Yes - Five year license |
| NEW CleverLauncher™ | Yes |
| NEW LynxShare™ | Yes |
| NEW LynxCloud™ | Yes |
| NEW Hardware Virtualisation | Yes |
| NEW NFC User Login | Yes |

Support & Installation

For all Clevertouch product support, visit: support.clevertouch.com The installation of this product should be completed by a qualified installer. Use of components not supplied by Clevertouch or not meeting minimum specifications may impact performance, safety and warranty. For more information, visit: clevertouch.com

Physical Spec

| Panel Dimensions | 65 " TBD 75 " TBD 86 " TBD | |
|-------------------|---|--|
| Packed Dimensions | 65 ″ TBD 75 ″ TBD 86 ″ TBD | |
| Net Weight | 65 " TBD 75 " TBD 86 " TBD | |
| Packed Weight | 65 " TBD 75 " TBD 86 " TBD | |
| VESA Mount Point | 65 " 600x400mm 75 " 800x400mm 86 " 800x600mm | |

Inside your Clevertouch Box

| 3 | |
|-------------------|----------------------------------|
| What's In The Box | (1) Clevertouch UX Pro Edge |
| | (1) 3M HDMI Cable |
| | (1) 3M Length USB cable (A-B) |
| | (1) 1.5M USB C Cable |
| | (1) 3M Regional Power Cable |
| | (1) Remote Control |
| | (2) Batteries for Remote Control |
| | (2) Dual Recognition Stylus |
| | (1) User Guide |
| | (1) Quick Install Guide |
| | (1) Clevertouch WiFi Module |

Warranty

Warranty term and upgrade options vary by region. Contact your local reseller or distributor for information and visit clevertouch.com/about/warranty

Compliance & Certification

| Regulatory Certification CE, FCC, UL, Er | ergy Star & EEC |
|--|-----------------|
|--|-----------------|











Statement

Size and weight vary by configuration and manufacturing process, please refer to the actual product. The product images are for illustrative purposes only and may slightly differ in appearance, colour, size, etc. from the actual product. The description, illustrations, etc. in this document may subject to change in accordance with the latest product specification and performance. Should the above-mentioned change in the document become necessary, the document may be updated without written notice.

© 2024 Clevertouch. All rights reserved. Sahara Presentations Systems PLC. is part of the Boxlight group of companies, and the owner of trademarks in several global jurisdictions including but not limited to Clevertouch, the Clevertouch logo, UX Pro, IMPACT™, IMPACT Plus™, Impact MAX, CleverLive, LUX, Lynx, CleverMessage, Cleverstore and Clevershare. All third-party trademarks (including logos and icons) referenced by Clevertouch remain the property of their respective owners. Unless specifically identified as such, Clevertouch's use of third-party trademarks does not indicate any relationship, sponsorship, or endorsement between Clevertouch and the owners of these trademarks. Applicable Terms and Conditions for warranty and support available at clevertouch.com/about/warranty. All weights and dimensions are approximate. Product specifications are subject to change without notice. Clevertouch.com.